

The 1200 mm flail mower with S30 quick attach bracket mounts only on the hydraulic side arm A448736. It cannot be mounted on the attachment coupling plate of the loader or on the A431070 S30 mechanical side arm - and on the other hand the normal flail mowers A36730 and A36015 cannot be mounted on the hydraulic side arm.

The S30 mower has otherwise the same 1200 mm mower deck with hammer flails as the A36730 flail mower, but it is equipped with the high flow hydraulic motor of the 1500 mm flail mower. This gives 25 % higher efficiency/working width ratio than on the 1500 mm flail mower, and 100 % higher than on the standard A36730 1200 mm flail mower.

- Easy mowing of road banks and gradients with the flail mower
- Outreach to the side max. 2,9 m
- Equipped with high flow hydraulic motor
- \$30 quick attach system



Working width					1200 mm	
Max. outreach to the side					2900 mm	
Max. width					1580 mm	
Weight, Fail mower S30					250 kg	
Weight, Flail mower with hydraulic side arm and side weights					680 kg	
Product no, Fail mower S30					A37505	
Product no, Flail mower with hydraulic side arm S30*					A37213	
*) Includes: Flail mower 1200 S30 Hydraulic side arm S30 Side weight kit 180 kg to side arm					A37505 A448736 A49063	
The optional Opticontrol® is required on the loader.						
550i	735	'55i	'60i	360i	5	9







adaptable









