



# Horse arena harrow

Electric Machine Compatible

The horse arena harrow is intended for levelling and loosening of horse arena riding surfaces. The harrow has two spring loaded tine rows which loosen the surface, a leveller that makes the surface completely even and a tilling roller that compacts the ground and leaves a finished surface perfectly suited for horse's hoof. The harrow doesn't damage the lower levels (understructure) of the riding surface.

The horse arena harrow features:

- A clearing shovel which takes away and levels the sand from the sides of the riding arena.
- A tilling roller that smoothens the harrowed ground and leaves a finished surface.
- A large wheel that protects the walls of the riding arena in case the harrow hits the wall.



Options:

- Manually operated support wheels, product no. A36593
- Hydraulically operated support wheels, product no. A37547. The loader must be equipped with the optional double acting rear auxiliary hydraulics outlet.
- Weights with handle, 29 kg, which can be mounted on the harrow to increase weight and make harrowing more efficient. With two weights the harrow works on almost any surface. The weight is the same extra weight as on Avant loader, product no. A35957.
- Water spraying system, product no. A37065
- Quick attach plate, look at page 182 A449060

- ✓ **A professional harrow that makes it easy to keep the horse arena in top condition**
- ✓ **Can be adjusted for several kinds of riding surfaces**
- ✓ **Once the adjustments have been done the harrow is very easy to use**
- ✓ **Two types of support wheels – manually or hydraulically operated – available as an option: the harrow can be lifted off the ground and towed to desired place**
- ✓ **Water spraying system available as an option, with 120 l water tank**

|                                      |         |
|--------------------------------------|---------|
| Working width                        | 1530 mm |
| Weight (without 29 kg extra weights) | 165 kg  |
| Product no                           | A21646  |

The optional Opticontrol® is required on the loader with water spraying system

|     |              |             |                |     |     |     |     |     |      |      |     |      |      |      |    |    |  |
|-----|--------------|-------------|----------------|-----|-----|-----|-----|-----|------|------|-----|------|------|------|----|----|--|
| 220 | 225          | 423         | 523            | 528 | 530 | 630 | 635 | 640 | 645i | 650i | 735 | 755i | 760i | 860i | e5 | e6 |  |
| ✓   | ✓            | ✓           | ✓              | ✓   | ✓   | ✓   | ✓   | ✓   | ✓    | ✓    | ✓   | ✓    | ✓    | ✓    | ✓  | ✓  |  |
| 162 | ✓ compatible | + adaptable | ✗ incompatible |     |     |     |     |     |      |      |     |      |      |      |    |    |  |

Compatibility tables are advisory. Please contact your local Avant UK DEALER to make sure that the attachment is compatible with your Avant loader.