

- Avant quick attach system for attachments (same as on other Avant models)
- Multi connector for hydraulic attachments (same as on other Avant models)
- Spacious cockpit: good legroom and storage space
- Multi function display: hour meter and fuel gauge, engine indicators, road traffic light indicators
- Hydrostatic 4WD
- Suspension seat with arm rests and heater standard in 225!
- Joystick 6 functions: auxiliary hydraulics control with buttons on joystick standard in 225!
- Self-levelling boom
- 14 I fuel tank
- Hydraulic oil cooler
- 47 Ah battery
- Automatic drive release
- LED front lights (1000 lumen)
- ✓ LED work light kit, on ROPS frame: 2 front, 1 rear (700 lumen)
- Avant 225 with 25 hp electronic fuel injection gasoline engine starts easily in any situation, no choke needed
- Auxiliary hydraulics oil flow to hydraulically driven attachments as high as 42 l/min

Safety

- Longer wheelbase and lower center of gravity better stability
- Certified ROPS safety frame and FOPS canopy
- Seat belt
- LED front lights as standard, extra LED work light kit (2 front, 1 rear, 700 lumen)
- Excellent, unrestricted field of vision to the attachment and working environment



1910 mm



700 kg



1400 mm



350 kg



15–18 kW / 20–25 hp gasoline



0 – 10 km/h

Specifications







Machine width

| Wheel size | Profile | Width |
|-----------------|-------------|---------|
| 20 x 8.00 - 10 | TR or grass | 995 mm |
| 20 x 8.00 - 10* | TR or grass | 1025 mm |

*) With spacers

| Model | AVANT 220 | AVANT 225 |
|---|--------------------------|--|
| Engine | Kohler CV640 Stage V | Kohler ECV730 EFI Stage V |
| Function | 4-stroke | 4-stroke, Electronic Fuel Injection |
| Fuel | gasoline | gasoline |
| Engine output (ECE R120) | 14,9 kW (20 hp) | 18,6 kW (25 hp) |
| Auxiliary hydraulics | | |
| Front outlet (standard) | 30 l/min | 42 I /min |
| Rear outlet (optional) | 7 l/min | 7 l /min |
| Drive speed | 0 - 10 km/h | 0 - 10 km/h |
| Wheels | 20x8.00-10 tractor/grass | 20x8.00-10 tractor/grass |
| Pulling force | 620 daN | 640 daN |
| Tipping load | 350 kg | 350 kg |
| Lifting height | 1400 mm | 1400 mm |
| Weight | 700 kg | 700 kg |
| Height | 1880 mm | 1880 mm |
| Width | 995/1025 mm | 995/1025 mm |
| Length | 1910 mm | 1910 mm |
| Product no: | M220 | M225 |